

Accessories


Busbar

Final Distribution

Technical Data

Standard	IEC 60664
Material of busbar	E-CU-F25
Material of insulation	PVC
Short-circuit strength	50kA
Nominal voltage	415V
Operating voltage	Max 500V
Surge voltage	4kV
Clima stability	IEC 60068-2

Order Information



Type	Pole	Thickness of pin (mm)	Section cross (mm ²)	Max. current(A) End feed-in	A	Length	Reference	Dimension(mm)
PIN-TYPE	1	1.5	10	63	7	1m	HBB16315P	
		1.5	16	80	11	1m	HBB18015P	
	2	1.5	10	63	7	1m	HBB26315P	
		1.5	16	80	11	1m	HBB28015P	
	3	1.5	10	63	7	1m	HBB36315P	
		1.5	16	80	11	1m	HBB38015P	
	4	1.5	10	63	7	1m	HBB46315P	
		1.5	16	80	11	1m	HBB48015P	
U-TYPE	1	1.5	10	63	7	1m	HBB16315F	
		1.5	16	80	11	1m	HBB18015F	
	2	1.5	10	63	7	1m	HBB26315F	
		1.5	16	80	11	1m	HBB28015F	
	3	1.5	10	63	7	1m	HBB36315F	
		1.5	16	80	11	1m	HBB38015F	
	4	1.5	10	63	7	1m	HBB46315F	
		1.5	16	80	11	1m	HBB48015F	



Type	Reference	Dimension(mm)
Terminal Adaptor	HBBA805	